# AIR QUALITY OPERATING PERMIT APPLICATION FORMS



## Prepared for:

Air Quality Permitted Facilities

#### By:

Idaho Division of Environmental Quality Air Quality Permitting Bureau Operating Permits Section

## **SECTION 1: GENERAL INFORMATION**

COMPANY & DIVISION NAME					
STREET ADDRESS OR P.O. BOX					
CITY					
STATE ZIP					
PERSON TO CONTACT					
TITLE					
PHONE NUMBER					
EXACT PLANT LOCATION					
GENERAL NATURE OF BUSINESS					
NUMBER OF FULL-TIME EMPLOYEES					
PROPERTY AREA (ACRES)			REASON FOR APF (1) Change of Own (2) Tier I Permit to (3) Tier II Permit to	ner or Location Operate	
DISTANCE TO NEAREST STATE BORDER (MILES)					
PRIMARY SIC			SECONDARY SIC		
PLANT LOCATION COUNTY			ELEVATION (FT)		
UTM ZONE					
UTM (X) COORDINATE (KM)			UTM (Y) COORDIN	IATE (KM)	
NAME OF FACILITIES List all facilities with the State that are under you		THER FACILITIES rol and have emissions	to the air. If none, so state	e.	
	]				
	]				
	]				
OWNER OR RESPONSIBLE OFFICIAL					
TITLE OF RESPONSIBLE OFFICIAL					
Based on information and belief formed after related to the statements and information in this SIGNATURE OF OWNER OR RESPONSIBLE	document are a	lete.		DATE	
The state of the s				57	

## **SECTION 2: FUEL BURNING EQUIPMENT**

14) PROPANE; 15) OTHER (SPECIFY)

DEQ USE ONLY					
DEQ PLANT ID CODE  DEQ BUILDING CODE  DEQ SEGMENT CODE		DEQ PROCESS CODE PRIMARY SCC		DEQ STACK ID CODE SECONDARY SCC	
PART A: GENERA	L INFORMATION				
PROCESS CODE OR DESCRIF	PTION				
STACK DESCRIPTION					
BUILDING DESCRIPTION					
MANUFACTURER		MODE	EL	DATE INSTALLED	
RATED C	CAPACITY (CHOOSE A	PPROPRIATE UNITS)		DATE LAST MODIFIED	
MILLION BTU/HR		1000 LBS STEAM/HR	KILOWATTS	HORSEPOW	/ER
BURNER TYPE		% USED FOR PROCESS			
_		% USED FOR SPACE HEAT			
FUEL DA	<b>ATA</b>				
PARAMETER	PRIMARY FUEL	UNITS	SECONDARY FUEL	UNITS	
FUEL CODE (SEE NOTE)		]			
PERCENT SULFUR		]			
PERCENT ASH		]		┚	
PERCENT NITROGEN		]			
PERCENT CARBON		]			
PERCENT HYDROGEN					
PERCENT MOISTURE		]			
HEAT CONTENT (BTU/UNIT)					
MAXIMUM HOURLY COMBUSTION RATE (UNITS/	HR)				
NORMAL ANNUAL COMBUSTION RATE (UNITS)	YR)				
NOTE: BURNER TYPE - 01) SF	PREAD STOKER; 02) CHAIN OF	R TRAVELING GRATE; 03) HAND	FIRED; 04) CYCLONE FURNACE;		
	05) WET BOTTOM (PULVERIZ	ZED COAL); 06) DRY BOTTOM (P	PULVERIZED COAL);		
	07) UNDERFEED STOKERS;	08) TANGENTIALLY FIRED; 09) F	HORIZONTALLY FIRED; 10) AXIALLY	FIRED;	
	11) OTHER (SPECIFY)			⊐	
FUEL CODES - 01) N.	ATURAL GAS; 02) #1 OR #2 FU	IEL OIL; 03) #4 FUEL OIL; 04) #5	OR #6 FUEL OIL; 05) USED OIL		
	06) WOOD CHIPS; 07) WOOD	BARK; 08) WOOD SHAVINGS; 0	9) SANDER DUST;		
	40) OURDITUMINOUS COM	44) DITUMINOUS COAL, 40) ANT	FUDACITE COAL. 42) LICNITE COAL		

## **SECTION 2, PART B**

NOTE:

DEDCENT FUE	OPERATING DATA EL CONSUMPTION PER QUARTER		OPERATING SCHED	N.II E			
DEC-FEB	LE GONGOIMI HONT EN GOARTEN		HOURS/DAY	, oll			
MAR-MAY			DAY/WEEK				
JUN-AUG			WEEKS/YEAR				
SEP-NOV							
PARAMETER TYPE TYPE CODE (F		PRIMARY		SECONDA	RY		
MODEL NUMB	ER						
	ROP (IN. OF WATER)						
	ER FLOW (GPM)				<del>-</del>		
	IR/CLOTH RATIO (FPM)				_		
27.07.00027							
	VENTILATION AND BUIL	DING/AREA DATA	STACI	K DATA			
ENCLOSED (Y	/N)?		GROUND ELEVATION	N (FT)			
HOOD TYPE (F	FROM APP. B)		UTM X COORDINAT	E (KM)			
MINIMUM FLO	W (ACFM)		UTM Y COORDINAT	E (KM)			
PERCENT CAP	PTURE EFFICIENCY		STACK TYPE (SEE N	NOTE BELOW)			
BUILDING HEI	GHT (FT)		STACK EXIT HEIGH	T FROM GROUND LEVEL (FT)			
BUILDING/ARE	EA LENGTH (FT)		STACK EXIT DIAME	TER (FT)			
BUILDING/ARE	EA WIDTH (FT)		STACK EXIT GAS FL	OWRATE (ACFM)			
			STACK EXIT TEMPE	RATURE (DEG. F)			
	AID DOLL LITANT FMICO	IONO					
POLLUTANT	CAS NUMBER	EMISSION FACTOR (SEE BELOW)	PERCENT CONTROL EFFICIENCY	ESTIMATED OR MEASURED EMISSIONS (LBS/HR)	ALL	OWABLE EMISSIO	ONS REFERENCE
PM							
PM-10							
SO2							
со							
NOX							
VOC							
LEAD							
		一					

STACK TYPE - 01) DOWNWARD; 02) VERTICAL (UNCOVERED); 03) VERTICAL (COVERED); 04) HORIZONTAL; 05) FUGITIVE EMISSION FACTOR IN LBS/UNITS. PLEASE USE SAME HOURLY UNITS GIVEN IN FUEL DATA SECTION.

## **SECTION 3: PROCESS AND MANUFACTURING OPERATIONS**

DEQ USE ONLY						
DEQ PLANT ID CODE		DEQ PROCESS COD	E	DEQ STACK ID CODE		
DEQ BUILDING CODE		PRIMARY SCC		SECONDARY SCC		
DEQ SEGMENT CODE						
PART A GENERA	L INFORMATION					
PROCESS CODE OR DESC	CRIPTION					
STACK DESCRIPTION						
BUILDING DESCRIPTION						
MANUFACTURER			MODEL		DATE INSTALLED	
					DATE LAST MODIFIED	
PROCES	SING DATA					
PROCESS STREAM	MATERIAL DESCRIPTION	MAXIMUM HOURLY RATE	ACTUAL HOURLY RATE	UNITS		
INPUT						
PRODUCT OUTPUT						
WASTE OUTPUT						
RECYCLE						
POTENTI	AL HAPS IN PROCES	SS STREAM(S)				
HAP DESCRIPTION		HAP CAS NUMBER	FRACTION IN INPUT STREAM BY WEIGHT	FRACTION IN PRODUCT STREAM BY WEIGHT	FRACTION IN WASTE STREAM BY WEIGHT	FRACTION IN RECYCLE STREAM BY WEIGHT

## **SECTION 3, PART B**

#### **OPERATING DATA**

PERCENT FUEL CONSUMPTION PER QUARTER	OPERATING SCHEDULE
DEC-FEB	HOURS/DAY
MAR-MAY	DAY/WEEK
JUN-AUG	WEEKS/YEAR
SEP-NOV	
POLLUTION CONTROL EQUIPMENT	
PARAMETER PRIMARY	SECONDARY
TYPE	
TYPE CODE (FROM APP. A)	
MANUFACTURER	
MODEL NUMBER	
PRESSURE DROP (IN. OF WATER)	
WET SCRUBBER FLOW (GPM)	
BAGHOUSE AIR/CLOTH RATIO (FPM)	
VENTILATION AND BUILDING/AREA DATA	STACK DATA
ENCLOSED (Y/N)?	GROUND ELEVATION (FT)
HOOD TYPE (FROM APP. B)	UTM X COORDINATE (KM)
MINIMUM FLOW (ACFM)	UTM Y COORDINATE (KM)
PERCENT CAPTURE EFFICIENCY	STACK TYPE (SEE NOTE BELOW)
BUILDING HEIGHT (FT)	STACK EXIT HEIGHT FROM GROUND LEVEL (FT)
BUILDING/AREA LENGTH (FT)	STACK EXIT DIAMETER (FT)
BUILDING/AREA WIDTH (FT)	STACK EXIT GAS FLOWRATE (ACFM)
	STACK EXIT TEMPERATURE (DEG. F)
AIR POLLUTANT EMISSIONS	
POLLUTANT CAS NUMBER EMISSION FACTOR	PERCENT ESTIMATED OR ALLOWABLE EMISSIONS CONTROL MEASURED
(SEE BELOW)	EFFICIENCY EMISSIONS (LBS/HR) (TONS/YR) REFERENCE (LBS/HR)
PM	
PM-10	
SO2	
со	
NOX	
voc	
LEAD	

## **SECTION 4: WASTE INCINERATION**

DEQ USE ONLY							
DEQ PLANT ID CODE		DEQ PROCESS CODE		D	EQ STACK ID CODE		]
DEQ BUILDING CODE		PRIMARY SCC		S	ECONDARY SCC		]
DEQ SEGMENT CODE							
PART A: GENERAL	. INFORMATION						
PROCESS CODE OR DESCRIF	PTION						]
STACK DESCRIPTION							]
BUILDING DESCRIPTION							]
MANUFACTURER		MODEL		D	ATE INSTALLED		]
				D	ATE LAST MODIFIED		
INCINERATOR TYPE			RATED HEATII	NG CAPACITY (N	MILLION BTU/HOUR)		_ ]
							_
PRIMARY	COMBUSTION CHAMB	ER DATA	-				
WASTE RETENTION TIME (MINUTES)		MINIMUM TEMPERATURE (E	DEG. F)		COMBUSTION AIR	FEED RATE (ACFM)	
BURNER TYPE		PERCENT OVERFIRE AIR			GAUGE F	PRESSURE (IN. H20)	
		PERCENT UNDERFIRE AIR					
PRIMARY	CHAMBER FUEL DATA						
PARAMETER	PRIMARY	UNITS		SECONDARY	UNITS		
FUEL CODE (SEE NOTE)	FUEL	Ī	Г	FUEL			
PERCENT SULFUR		I 					
		<u> </u> 					
PERCENT ASH		l I	L				
PERCENT NITROGEN		<u> </u>	L				
PERCENT CARBON		<u> </u>	L				
PERCENT HYDROGEN		-	Ļ				
PERCENT MOISTURE			L				
HEAT CONTENT (BTU/UNIT)			] [				
MAXIMUM HOURLY COMBUSTION RATE (UNITS/	HR)		] [				
NORMAL ANNUAL COMBUSTION RATE (UNITS)			] [				
NOTE: INCINERATOR TYPE	01) SINGLE CHAMBER; 02) MU	LTIPLE HEARTH; 03) ROTARY	Y KILN; 04) FLUI	DIZED BED;			
	05) OTHER (SPECIFY)	. ,	, ,				
BURNER TYPE - 01)	AXIAL FIRING; 02) RADIAL FIRIN	NG; 03) TANGENTIAL FIRING;					
	04) OTHER (SPECIFY)						
FUEL CODES - 01) N	ATURAL GAS; 02) #1 OR #2 FUE	EL OIL; 03) #4 FUEL OIL; 04) #	5 OR #6 FUEL O	OIL; 05) PROPANI	E		
	06) OTHER (SPECIFY)						

## **SECTION 4, PART A**

#### SECONDARY COMBUSTION CHAMBER DATA

COMBUSTION CHAMBER		MINIMUM		COMBUSTION AIR	
VOLUME (CUBIC FEET)		TEMPERATURE (DEG. F)		FEED RATE (SCFM)	
GAUGE PRESSURE (INCHES WATER)		BURNER TYPE (1) AXIAL FIRING (2) RADIAL FIRING (3) TANGENTIAL FIRING (4) OTHER			
SECONDARY PRIMA	RY CHAMBER FUEL DA	TA			
PARAMETER	PRIMARY FUEL	UNITS	SECONDARY FUEL	UNITS	
FUEL CODE (SEE NOTE)					
PERCENT SULFUR					
PERCENT ASH					
PERCENT NITROGEN					
PERCENT CARBON					
PERCENT HYDROGEN					
PERCENT MOISTURE					
HEAT CONTENT (BTU/UNIT)					
MAXIMUM HOURLY COMBUSTION RATE (UNITS/HR)					
NORMAL ANNUAL COMBUSTION RATE (UNITS/YR)					
NOTE: INCINERATOR TYPE(01) SINGLE	CHAMBER; 02) MULTIPLE HEAI	RTH; 03) ROTARY KILN; 04) F	LUIDIZED BED;		
05) OTHER	SPECIFY)				
BURNER TYPE - 01) AXIAL FIRING		ENTIAL FIRING;			
04) OTHER	SPECIFY)				
FUEL CODES - 01) NATURAL GAS	; 02) #1 OR #2 FUEL OIL; 03) #4	FUEL OIL; 04) #5 OR #6 FUE	L OIL; 05) PROPANE		
06) OTHER	SPECIFY)				
PRIMARY CHAMBER	MONITORING AND COI	MBUSTION CONTROL	s		
SECONDARY CHAME	ER MONITORING AND	COMBUSTION CONTI	ROLS		

# **SECTION 4, PART A**

#### WASTE CHARACTERIZATION AND COMBUSTION RATE

PARAMETER	PRIMARY FUEL	UNITS	SECONDARY FUEL	UNITS
WASTE DESCRIPTION				
PERCENT SULFUR				
PERCENT ASH				
PERCENT NITROGEN				
PERCENT CARBON				
PERCENT HYDROGEN				
PERCENT MOISTURE				
HEAT CONTENT (BTU/UNIT)				
MAXIMUM HOURLY COMBUSTION RATE (UNITS/HR)				
NORMAL ANNUAL COMBUSTION RATE (UNITS/YR)				
METHOD OF ASH DISPOSAL				
POTENTIAL HAPS IN W	/ASTES			
HAP DESCRIPTION	HAP CAS NUMBER	FRACTION IN WASTE FEED BY WEIGHT	FRACTION IN BOTTOM ASH BY WEIGHT	FRACTION IN FLY ASH BY WEIGHT

#### **SECTION 4, PART B**

#### **OPERATING DATA** PERCENT FUEL CONSUMPTION PER QUARTER OPERATING SCHEDULE DEC-FEB HOURS/DAY MAR-MAY DAY/WEEK WEEKS/YEAR JUN-AUG SEP-NOV **POLLUTION CONTROL EQUIPMENT** PARAMETER SECONDARY TYPE TYPE CODE (FROM APP. A) MANUFACTURER MODEL NUMBER PRESSURE DROP (IN. OF WATER) WET SCRUBBER FLOW (GPM) BAGHOUSE AIR/CLOTH RATIO (FPM) **VENTILATION AND BUILDING/AREA DATA** STACK DATA ENCLOSED (Y/N)? GROUND ELEVATION (FT) HOOD TYPE (FROM APP. B) UTM X COORDINATE (KM) MINIMUM FLOW (ACFM) UTM Y COORDINATE (KM) PERCENT CAPTURE EFFICIENCY STACK TYPE (SEE NOTE BELOW) STACK EXIT HEIGHT FROM GROUND LEVEL (FT) BUILDING HEIGHT (FT) BUILDING/AREA LENGTH (FT) STACK EXIT DIAMETER (FT) STACK EXIT GAS FLOWRATE (ACFM) BUILDING/AREA WIDTH (FT) STACK EXIT TEMPERATURE (DEG. F) AIR POLLUTANT EMISSIONS POLLUTANT CAS NUMBER **EMISSION** PERCENT ESTIMATED OR ALLOWABLE EMISSIONS FACTOR (SEE BELOW) CONTROL EFFICIENCY MEASURED EMISSIONS (LBS/HR) REFERENCE (TONS/YR) (LBS/HR) PM PM-10 SO<sub>2</sub> CO NOX VOC LEAD

NOTE: STACK TYPE - 01) DOWNWARD; 02) VERTICAL (UNCOVERED); 03) VERTICAL (COVERED); 04) HORIZONTAL; 05) FUGITIVE EMISSION FACTOR IN LBS/UNITS. PLEASE USE SAME HOURLY UNITS GIVEN IN FUEL DATA SECTION.

## SECTION 5: STORAGE AND HANDLING OF LIQUID SOLVENTS & OTHER VOLATILE COMPOUNDS

DEQ USE ONLY								
DEQ PLANT ID CODE		DEQ PROCESS CODE			DEQ STACK ID COD	E		]
DEQ BUILDING CODE		PRIMARY SCC			SECONDARY SCC			]
DEQ SEGMENT CODE								
PART A: GENERAL IN	IFORMATION							
PROCESS CODE OR DESCRI	PTION							]
STACK DESCRIPTION								]
BUILDING DESCRIPTION								]
DATE INSTALLED		DATE LAST MODIFIED						
GENERAL TA	ANK AND MATERIAL H	ANDLING DATA						
MATERIAL DESCRIPTION								
TANK CAPACITY (GALLONS)		ANNUAL THROUGHPUT (	GALLONS)		]			
TANK TYPE  PLEASE CHOOSE FROM BEL (01) FIXED ROOF (02) FLOATING ROOF (OR I (03) VARIABLE VAPOR SPA (04) PRESSURE TANK (05) UNDERGROUND - SPL (06) OTHER	NTERNAL COVER) CE		SOURCE PLEASE CHOOS (01) PIPELINE (02) RAIL CAR (03) TANK TRU (04) SHIP BAR (05) OTHER	JCK	] w			]
ADDITIONAL	. VAPOR PHASE DEGR	EASING DATA						
MANUFACTURER OF DEGRE					TANK SURFACE	E AREA (SQ	ı. FT)	
TEMPERATURE OF DEGREA	SING AGENT IN TANK (DEG	. F)			METHOD OF VA Please choose from (01) Incineratio (02) Refrigerate (03) Refrigerate (04) Carbon Ad (05) Vapor Reti (06) No Recove (07) Other	om below: n ed Liquid Sc ed Condens Isorption urn System	crubber	
ADDITIONAL	. MATERIAL HANDLING	DATA						
PHYSICAL STATE		NUMBER OF PUMP SEALS		NUMBER OF VALVES	IN-LINE		NUMBER OF SAF RELIEF VALVES	ETY
NUMBER OF		NUMBER OF SAMPLING		***************************************			NUMBER OF SAM	IPLING
OPEN-ENDED LINES		CONNECTIONS					CONNECTIONS	
MATERIAL D	)ATA							
HAP DESCRIPTION				HAP CAS NUMBER	] ] ]		HAP FRACTION IN MATERIAL BY WEIGHT	] ] ]
					]			]

#### **SECTION 5, PART B**

NOTE:

#### **OPERATING DATA** PERCENT FUEL CONSUMPTION PER QUARTER OPERATING SCHEDULE DEC-FEB HOURS/DAY MAR-MAY DAY/WEEK WEEKS/YEAR JUN-AUG SEP-NOV **POLLUTION CONTROL EQUIPMENT** PARAMETER SECONDARY TYPE TYPE CODE (FROM APP. A) MANUFACTURER MODEL NUMBER PRESSURE DROP (IN. OF WATER) WET SCRUBBER FLOW (GPM) BAGHOUSE AIR/CLOTH RATIO (FPM) **VENTILATION AND BUILDING/AREA DATA** STACK DATA ENCLOSED (Y/N)? GROUND ELEVATION (FT) HOOD TYPE (FROM APP. B) UTM X COORDINATE (KM) MINIMUM FLOW (ACFM) UTM Y COORDINATE (KM) PERCENT CAPTURE EFFICIENCY STACK TYPE (SEE NOTE BELOW) STACK EXIT HEIGHT FROM GROUND LEVEL (FT) BUILDING HEIGHT (FT) BUILDING/AREA LENGTH (FT) STACK EXIT DIAMETER (FT) STACK EXIT GAS FLOWRATE (ACFM) BUILDING/AREA WIDTH (FT) STACK EXIT TEMPERATURE (DEG. F) AIR POLLUTANT EMISSIONS POLLUTANT CAS NUMBER **EMISSION** PERCENT ESTIMATED OR ALLOWABLE EMISSIONS FACTOR (SEE BELOW) CONTROL EFFICIENCY MEASURED EMISSIONS (LBS/HR) REFERENCE (TONS/YR) (LBS/HR) PM PM-10 SO<sub>2</sub> CO NOX VOC LEAD

STACK TYPE - 01) DOWNWARD; 02) VERTICAL (UNCOVERED); 03) VERTICAL (COVERED); 04) HORIZONTAL; 05) FUGITIVE EMISSION FACTOR IN LBS/UNITS. PLEASE USE SAME HOURLY UNITS GIVEN IN FUEL DATA SECTION.

## **SECTION 6: LOADING RACKS**

AVERAGE MATERIAL TEMPERATURE (DEG. F)

DEQ USE ONLY				
DEQ PLANT ID CODE	DEQ PROCESS CODE		DEQ STACK ID CODE	
DEQ BUILDING CODE	PRIMARY SCC		SECONDARY SCC	
DEQ SEGMENT CODE				
PART A: LOADING RACK DATA				
PROCESS CODE OR DESCRIPTION				
STACK DESCRIPTION				
BUILDING DESCRIPTION				
DATE INSTALLED		DATE MO	DIFIED	
TYPE OF LOADING  Please choose from the following: (01) Overhead loading - splash fill, normal service (02) Overhead loading - splash fill, balanced service (03) Overhead loading - submerged fill, normal service (04) Overhead loading - submerged fill, balanced (05) Bottom loading - normal service; (06) Bottom loading - balanced service	viced; ervice;	Please c (01) In (02) G (03) Sc (04) Cl	HICKSAN one - open to air	
MATERIAL LOADED				
ANNUAL THROUGHPUT (GAL.)				
REID VAPOR PRESSURE (PSI)				
MAXIMUM MATERIAL TEMPERATURE (DEG. F)				

#### **SECTION 6, PART B**

#### **OPERATING DATA** PERCENT FUEL CONSUMPTION PER QUARTER OPERATING SCHEDULE DEC-FEB HOURS/DAY MAR-MAY DAY/WEEK WEEKS/YEAR JUN-AUG SEP-NOV **POLLUTION CONTROL EQUIPMENT** PARAMETER SECONDARY TYPE TYPE CODE (FROM APP. A) MANUFACTURER MODEL NUMBER PRESSURE DROP (IN. OF WATER) WET SCRUBBER FLOW (GPM) BAGHOUSE AIR/CLOTH RATIO (FPM) **VENTILATION AND BUILDING/AREA DATA** STACK DATA ENCLOSED (Y/N)? GROUND ELEVATION (FT) HOOD TYPE (FROM APP. B) UTM X COORDINATE (KM) MINIMUM FLOW (ACFM) UTM Y COORDINATE (KM) PERCENT CAPTURE EFFICIENCY STACK TYPE (SEE NOTE BELOW) STACK EXIT HEIGHT FROM GROUND LEVEL (FT) BUILDING HEIGHT (FT) BUILDING/AREA LENGTH (FT) STACK EXIT DIAMETER (FT) STACK EXIT GAS FLOWRATE (ACFM) BUILDING/AREA WIDTH (FT) STACK EXIT TEMPERATURE (DEG. F) AIR POLLUTANT EMISSIONS POLLUTANT CAS NUMBER **EMISSION** PERCENT ESTIMATED OR ALLOWABLE EMISSIONS FACTOR (SEE BELOW) CONTROL EFFICIENCY MEASURED EMISSIONS (LBS/HR) REFERENCE (TONS/YR) (LBS/HR) PM PM-10 SO<sub>2</sub> CO NOX VOC LEAD

NOTE: STACK TYPE - 01) DOWNWARD; 02) VERTICAL (UNCOVERED); 03) VERTICAL (COVERED); 04) HORIZONTAL; 05) FUGITIVE EMISSION FACTOR IN LBS/UNITS. PLEASE USE SAME HOURLY UNITS GIVEN IN FUEL DATA SECTION.

## SECTION 7: SOLID MATERIAL TRANSPORT, HANDLING, AND STORAGE

DEQ USE ONLY						
DEQ PLANT ID CODE		DEQ PROCESS CODE		DEQ STACK ID CODE		
DEQ BUILDING CODE		PRIMARY SCC		SECONDARY SCC		
DEQ SEGMENT CODE						
PART A: GENERAL	INFORMATION					
PROCESS CODE OR DESC						
STACK DESCRIPTION						
BUILDING DESCRIPTION						
DATE INSTALLED OR LAS	T MODIFIED		DATE LAST MODIFIED			
MATERIAL DESCRIPTION						
MATERIAL	. TRANSFER RATES					
MAXIMUM HOURLY TRAN		T				
NORMAL HOURLY TRANS	·					
NORMAL ANNUAL TRANS						
UNIT OF MEASURE	. 2					
BELT CON	IVEYOR/VEHICLE TF	RANSFER				
NUMBER OF TRANSFERS		MATERIAL MOISTURE CONTENT (WEIGHT PERC	ENT)	MAXIMUM HOURLY WIND SPEED (MPH)		
CONVEYORS ENCLOSED	? (Y/N)		CONVEYORS IN BUILDI	NGS? (Y/N)	AVERAGE HOURLY	
TRANSFERS ENCLOSED?	(Y/N)		TRANSFERS IN BUILDIN	NGS? (Y/N)	WIND SPEED (MPH	)
PNEUMAT	IC CONVEYOR TRAI	NSFERS				
MATERIAL MOISTURE CO	NTENT (WEIGHT PERCE	ENT)				
PRIMARY SEPARATOR TY	PE		PRIMARY SEPARATOR	PERCENT EFFICIENCY		
SECONDARY SEPARATOR	R TYPE		SECONDARY SEPARAT	OR PERCENT EFFICIENCY		
MATERIAL	STORAGE DATA					
PILE? (Y/N)		STORA	AGE CAPACITY		PILE LENGTH (FT.)	
SILO? (Y/N)		STORA	AGE CAPACITY UNITS		PILE WIDTH (FT.)	
OTHER STORAGE TYPE D	DESCRIPTION				PILE HEIGHT (FT.)	
					,	
MATERIAL	. DATA					
HAP DESCRIPTION			HAP CAS NUMBER		HAP FRACTION IN MATERIAL BY WEIGHT	
		]				
		]				
		1				
		<u>-</u> 1				
		_				
1						

#### **SECTION 7, PART B**

#### **OPERATING DATA** PERCENT FUEL CONSUMPTION PER QUARTER OPERATING SCHEDULE DEC-FEB HOURS/DAY MAR-MAY DAY/WEEK WEEKS/YEAR JUN-AUG SEP-NOV **POLLUTION CONTROL EQUIPMENT** PARAMETER SECONDARY TYPE TYPE CODE (FROM APP. A) MANUFACTURER MODEL NUMBER PRESSURE DROP (IN. OF WATER) WET SCRUBBER FLOW (GPM) BAGHOUSE AIR/CLOTH RATIO (FPM) **VENTILATION AND BUILDING/AREA DATA** STACK DATA ENCLOSED (Y/N)? GROUND ELEVATION (FT) HOOD TYPE (FROM APP. B) UTM X COORDINATE (KM) MINIMUM FLOW (ACFM) UTM Y COORDINATE (KM) PERCENT CAPTURE EFFICIENCY STACK TYPE (SEE NOTE BELOW) STACK EXIT HEIGHT FROM GROUND LEVEL (FT) BUILDING HEIGHT (FT) BUILDING/AREA LENGTH (FT) STACK EXIT DIAMETER (FT) STACK EXIT GAS FLOWRATE (ACFM) BUILDING/AREA WIDTH (FT) STACK EXIT TEMPERATURE (DEG. F) AIR POLLUTANT EMISSIONS POLLUTANT CAS NUMBER **EMISSION** PERCENT ESTIMATED OR ALLOWABLE EMISSIONS FACTOR (SEE BELOW) CONTROL EFFICIENCY MEASURED EMISSIONS (LBS/HR) REFERENCE (TONS/YR) (LBS/HR) PM PM-10 SO<sub>2</sub> CO NOX VOC LEAD

NOTE: STACK TYPE - 01) DOWNWARD; 02) VERTICAL (UNCOVERED); 03) VERTICAL (COVERED); 04) HORIZONTAL; 05) FUGITIVE EMISSION FACTOR IN LBS/UNITS. PLEASE USE SAME HOURLY UNITS GIVEN IN FUEL DATA SECTION.

## **SECTION 8: FUGITIVE ROAD DUST SOURCES**

DEQ USE ONLY					
DEQ PLANT ID CODE	DEQ PROCESS CODE		DEQ STACK ID CODE		
DEQ BUILDING CODE	PRIMARY SCC		SECONDARY SCC		
DEQ SEGMENT CODE					
PART A: GENERAL INFORMATION					
ROAD DESCRIPTION		PAVED? (Y/N)			
LENGTH (FT.)		BEGINNING UTM-X (KM)	COORDINATES UTM-Y (KM)	END COC UTM-X (KM)	ORDINATES UTM-Y (KM)
WIDTH (FT.)					
DATA FOR ALL ROADS - PAVE	O AND UNPAVED				
VEHICLE DESCRIPTION	NUMBER OF ROUNDTRIPS PER DAY	VEHICLE MILES TRAVELED PER DAY	NUMBER OF DAYS PER YEAR USED	AVERAGE VEHICLE SPEED (MPH)	SURFACE SILT CONTENT (% WEIGHT)
				DATA: UNPAVED	ROADS
VEHICLE DESCRIPTION	VEHICLE EMPTY WEIGHT	VEHICLE FULL WEIGHT		NUMBER OF WHEELS PER VEHICLE	NUMBER OF DAYS >0.01 INCHES
	(TONS)	TONS			PRECIPITATION
DATA: PAVED ROADS					
NUMBER OF INDUSTRIAL LANES AUGMENTATION FACTOR	DUST LOADING (LB/MILE)				
ROAD DUST CHEMICAL DATA					
HAP DESCRIPTION		HAP CAS NUMBER		HAP FRACTION IN ROAD DUST	
				BY WEIGHT	

## **SECTION 8, PART B**

#### **OPERATING DATA** PERCENT FUEL CONSUMPTION PER QUARTER OPERATING SCHEDULE DEC-FEB HOURS/DAY MAR-MAY DAY/WEEK JUN-AUG WEEKS/YEAR SEP-NOV **FUGITIVE DUST CONTROL DATA** PARAMETER PRIMARY SECONDARY CONTROL DESCRIPTION CONTROL CODE (APPENDIX A) MINIMUM DAILY APPLICATIONS OF CONTROL MAXIMUM DAILY APPLICATIONS OF CONTROL AVERAGE ANNUAL APPLICATIONS OF CONTROL AMOUNT APPLIED (UNITS/APPLICATION) UNITS FOR APPLICATION AMOUNT

## AIR POLLUTANT EMISSIONS

POLLUTANT	CAS NUMBER	EMISSION FACTOR (SEE BELOW)	PERCENT CONTROL EFFICIENCY	ESTIMATED OR MEASURED EMISSIONS (LBS/HR)	ALLOWABLE EMISSIONS		
					(LBS/HR)	(TONS/YR)	REFERENCE
PM							
PM-10							
LEAD							

NOTES: IN LBS/UNIT. USE UNITS OF VEHICLE MILES TRAVELED (VMT).